



GRAUER & WEIL (INDIA) LTD.
Unit : Bombay Paints



BPL MARINE BD COATING

DESCRIPTION

BPL MARINE BD COATING is an alkyd based paint which is resistant to sunlight, seawater & splashes of oil.

TYPICAL USE

As a finishing coat on boot top areas & decks

PRODUCT DATA

APPLICATION

Airless Spray, Air Spray and Brush

NOZZLE ORIFICE

0.018"

NOZZLE PRESSURE

2180 psi

VOLUME SOLIDS

44%

RECOMMENDED DFT

30 microns

CORRESPONDING WFT

75 microns

THEORETICAL SPREADING

RATE AT ABOVE DFT

14.6 M²/ Ltr

DRYING-SURFACE DRY

4 hrs

COLOUR

Red /Green

FINISH

Semi glossy

FLASH POINT

30° C

SHELF LIFE

12 months

OVERCOAT INTERVAL

Min 8 hrs, Max. none

PRECEEDING COAT

BPL MARINE PRIMER

APPLICATION CONDITIONS

As dictated by any good painting practice

SAFETY

As a general rule, avoid inhalation of solvent vapour or paint mist and contact of liquid paint with skin and eyes. Provide forced ventilation when working with solvent borne coating in confined spaces or stagnant air. Provide respiratory, skin & eye protection. Follow local and national safety regulations.

ISSUE

JANUARY 2007.

M-1-G.