



PENTOLITE SUPER SYNTHETIC ENAMEL

DESCRIPTION..

PENTOLITE SUPER SYNTHETIC ENAMEL is high gloss premium enamel based on synthetic resin and selected weather resistant pigments for decoration and protection of internal and external surfaces. This premium quality high gloss enamel has very good colour retention and water resistance. On account of high covering capacity and ease of brushing it is ideally for sign board painting.

TYPICAL USE ..

As a general purpose finishing coat on exterior steel surface in mild to moderately corrosive environment and interior wood work and steel.

PRODUCT DATA :

APPLICATION	Brush, Air Spray, Roller, Dip
VOLUME SOLIDS	35 %
FINISH	Glossy
RECOMMENDED DFT	25 microns
CORRESPONDING WFT	75 microns
THEORETICAL SPREADING RATE	14 M ² /Ltr at above DFT
DRYING – TOUCH DRY	1 – 2 hrs
HARD DRY	4 – 5 hrs
COLOUR	White, Assorted
OVERCOAT INTERVAL	Min 12 hrs Max None
FLASH POINT	Above 30°C
THINNER	100
SHELF LIFE	12 months
PRECEDING COAT	Kangaroo Metal Primer or Similar Primer as per substrate.

:: 2 :: PENTOLITE SUPER SYNTHETIC ENAMEL

SURFACE PREPARATION

The surface to be painted should be dry and free from rust, grease, oil & loose particles. After application of suitable primer two or more coats to be applied allowing an interval of 8 / 10 hrs. between subsequent coats.

HEALTH & SAFETY

As a general rule, avoid inhalation of solvent vapours or paint mist and contact of paint with skin and eyes. Provide forced ventilation when working with solvent borne coating in confined spaces or stagnant air. Also provide respiratory, skin and eye protection. Also follow local and national safety regulations.

ISSUE

AUGUST - 2006.