



RANGEELA SYNTHETIC ENAMEL

DESCRIPTION..

RANGEELA SYNTHETIC ENAMEL is based on a Synthetic Resin, specially formulated to give gloss and durability, at a low cost. It has excellent brush ability and opacity.

TYPICAL USE..

As a finishing coat for Interior surface such as wood or steel, Office equipment, machinery etc.

PRODUCT DATA :

| | | |
|----------------------------|----|--|
| APPLICATION | .. | Air Spray, Brush |
| VOLUME SOLIDS | .. | 25% |
| FINISH | .. | Glossy |
| RECOMMENDED DFT | .. | 25 Microns |
| CORRESPONDING WFT | .. | 75 Microns |
| THEORETICAL SPREADING RATE | .. | 10 M ² /Ltr At Above DFT |
| DRYING – TOUCH DRY | .. | 2 - 4 hrs |
| HARD DRY | .. | 4 – 5 hrs |
| COLOUR | .. | White , Assorted |
| RECOATING INTERVAL | .. | After 8 Hours |
| FLASH POINT | .. | Above 30°C |
| THINNER | .. | 100 |
| SHELF LIFE | .. | 12 Months |
| SURFACE PREPARATION | .. | The surface to be painted should be dry and free from rust, grease, oil & loose particles. After application of suitable primer two or more coats are to be applied. |
| ISSUE | .. | AUGUST 2006 |

A-1-B.